Monster assimilation and adaptation in FRM: High Beck fluvial flood-mitigation case study



Onno Bokhove [Leeds Inst. Fluid Dynamics, UK] EGU-2024, Vienna, EU

Bokhove, Leeds Institute for Fluid Dynamics, UK

Uncertainty monsters in Flood-Risk Management (FRM)

Knotters et al. (2024) use the monster metaphor to propose six (coping) strategies to deal with uncertainties FRM. **Monster**

- exorcism, reduce uncertainty even if it is not realisable.
- embracement, trivialization by magnifying uncertainties.
- denial, <u>Concorde effect</u>: limited viability yet continued investment, e.g., of some NFM (upscaling fails, e.g. using beavers) of higher-and-higher flood walls.
- anesthesia, uncertainty "prevented" by striving for consensus or agreeing about quality of information.
- adaptation, adjust uncertainty, rationalise risk mitigation & optimise chosen utility (function). UK-EA: blended approach.
- assimilation, learn from uncertainty (quantification) & accordingly make changes.

Bokhove, Leeds Institute for Fluid Dynamics, UK

High Beck flood-mitigation case study (50yrs)

- Square-lake plots: size & costs with flood-excess volume & mitigation measures.
- Base costs q_i , probability failure p_i , repair costs q_{p_i} , i = 1, 2, 3; costs $q_i + p_i q_{p_i}$.
- Combine Canal C1, bund B2, flood-plain-storage FP3 into 5 scenarios:



• Utility functions: $U_1 = \sum_{j=1}^5 w_j C_j$, $U_2 = \sum_{j=1}^5 (w_j C_j - \sum_{k=1}^{N_j} \alpha_{kj} B_{jk})$ (co-benefits B_{jk} : e.g., droughts, extra CC, less pollution), decision tree.

Difficult to get 9 values but U₂ yields new insights on appreciating benefits.

Bokhove, Leeds Institute for Fluid Dynamics, UK

High Beck setting: mock (stylised real) case study

- High Beck is a partly culverted urban beck, circa 2000m in length from spring to main river with a 100m drop, it goes under and/or flows into a canal, with a culverted last 200m.
- Surface flooding occurs in neighbourhood culverts near the river at a 1:10yrs AEP.
- New flood defence walls near river cover 1:200yrs AEP. Then beck water trapped: limited pump action Q_T ≤ 0.245m³/s.
- Surface flooding of neighbourhood culverts near river stays 1:10yrs AEP with new flood walls.
- Canal segment for large <u>flood storage</u> between two locks is 7.5km × 10m × 1.5m with several overflows.
- A combined sewer overflow (CSO) pollutes intermittently in beck; stretch from CSO to canal is 200m; extra anti-CSO-pollution measures possible.

500

Bokhove, Leeds Institute for Fluid Dynamics, UK

High Beck: flood-excess volume

Numerical modelling 1:50yrs High Beck flood (no field data); flood-excess-volume during event:

$$FEV = \int_{t_0}^{t_0+T} Q(t) - Q_T dt = 9600 \text{m}^3 = 98 \times 98 \times 1\text{m}^3$$
 (sense of size!)



Bokhove, Leeds Institute for Fluid Dynamics, UK

Flood-mitigation measures

Council is exploring three measures to reduce FEV (i.e., the flood damage) to zero, each with basic construction costs q_i :

- ▶ C1: Beck flow diverted into canal, automated gate to divide water into canal/culvert, coverage of $\alpha_1 FEV$ with $\alpha_1 > 1$, cost $q_1 + p_1 q_{p_1}$.
- **B2**: Upstream bund in flatter areas, partial prevention $\alpha_2 FEV$ with $\alpha_2 = 0.4$, cost $q_2 + p_2 q_{p_2}$.
- FP3: Culvert from canal to river to be opened at playing fields (protective bunds), pumping needed, partial prevention, α₃FEV with α₃ = 0.6, cost q₃ + p₃q_{p₃}.



Bokhove, Leeds Institute for Fluid Dynamics, UK

Monster risks M1-M5

Failure probabilities p_i and damage q_{p_i} :

- M1: Fear of berm/culvert collapse of Victorian-age canal C1 (already present), costs p₁q_{p₁}; fear and ignorance. Hitherto, impossible to get data or values from the "Trust" ... (language barriers).
- M2: Berm collapse of bund B2 can cause flood wave on steep slopes, costs p₂q_{p₂}, a priori unknown.
- M3: Failure of bunds in FP3 but chance low, clearing of flood debris and pollution by sewage, costs p₃q_{p3}, a priori unknown.
- M4: Subjective rejections and co-benefits can act as monsters and fairies. Hydrographs, probabilities and costs contain uncertainties. How do we quantify these?
- M5: Multi-benefit canal option may become impossible because the involved parties: i.e., Council, water company Shire and Trust (legally), do not and cannot agree on solving sewage-release, flooding, drought and ecological aspects? A case of monster anesthesia?

Bokhove, Leeds Institute for Fluid Dynamics, UK

Flood-mitigation scenarios

Combinations of C1, B2 and FP3 yield the following five scenarios (over 50 yrs):

- Canal C1: with excess coverage.
- Bund & canal B2+FP3: 1.0 × FEV only and pumping needed.
- Flood-plain storage & canal FP3+C1: excess coverage, pumping optional depending on CSO-assessment.
- B2+C1: excess coverage, pumping optional depending on CSO-assessment.
- All B2+FP3+C1: excess coverage, pumping optional depending on CSO-assessment.
- Benefits C1: drought measure, refreshes canal, extra storage for climate change; danger: CSO spills unless CSO and beck split for 200m from CSO to canal, extra costs B₁₁ ∝ −q_{1,CSO}.



Bokhove, Leeds Institute for Fluid Dynamics, UK

Discussion: good and bad decisions

What are suboptimal decisions? These are decisions that:

- lead to new problems, e.g. loss of ecological functions;
- lead to unintended consequences, e.g. high flood-defense walls lead to a false sense of security (under climate change) and can trap water inside a city; and,
- have an uneven distribution of costs and benefits when other sectors and social groups are taken into account. How does one take these into account?

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 シののや

Bokhove, Leeds Institute for Fluid Dynamics, UK

Decision-taking criteria

Morgan and Henrion (1990) discuss several decision-taking criteria:

- utility-based (deterministic/probabilistic cost, cost-effectiveness, bounded cost, multi-attribute, ...)
- rights-based (zero/bounded/constrained risk, compensation),
- technology-based using the "best available technology",
- hybrid criteria (combine the above), and
- an "approved process" (a suboption of a rights-based criterion) when a decision is acceptable when a specified set of procedures is met (for which decision analysis is inappropriate or pointless). Are approved processes common, in which one can hide issues behind set procedures?

Bokhove, Leeds Institute for Fluid Dynamics, UK

Base costs, probabilities and damage costs

Measure	$q_i \; (k \pounds)$	p_i (/50yrs)	q_{p_i} (k£)
C1	500 (900)	1	70
B2	<u>385</u>	0.25	200
FP3	<u>400</u>	0.05	200

Table: To obtain an estimate for q_1 , we start from the £1.7M repair costs of a culvert breach, emptying 60km of the Leeds-Liverpool canal (2021-2022). Since the canal stretch involved in FP3 is 7km 1/8th of those costs are involved so circa £210.000, of which £140.000 are standard costs occurring even in the absence of flood storage in the canal and £70.000 as extra investment. The latter costs are put forward. The base cost for C1 are £500.000 plus extra costs for the optional 200m pipeline to separate the CSO from the beck. In that case FP3 could be excluded to avoid pollution of the playing fields. Except for the real $q_2 + q_3 = k \pounds785$ figure given all other costs are made up pending ongoing investigations. (https://www.newcivilengineer.com/latest/

work-begins-on-1-7m-scheme-to-repair-breached-leeds-liverpool-canal-18-01-2022/) と くきと き つうへの Bokhove, Leeds Institute for Fluid Dynamics, UK

Utility functions, assigning values, uncertainty

- The costs for the five scenarios are (using values of Table): C1: £570k (£970k with CSO-clean-up); B2+FP3: £845k; B2+C1: £1005k (1405k£); FP3+C1: £980 (£1380k); B2+FP3+C1: £1405k (£1805k).
- ► Take B₁₁ = -q_{1CSO} (less or no pollution in beck/canal); B₁₂ = q_{1cc} (extra climate-change flood-plain storage); B₁₃ = q_{1D} (drought benefits beck flow into canal); B₁₄ = q_{1E} (ecological value beck water into canal); B₁₅ = q_{1clean} (clean beck and canal).
- Using utility function U₁ = ∑_{j=1}⁵ w_jC_j the optimal weights for minimal costs are:
 (a) w₁ = 1 and w₂ = w₃ = w₄ = w₅ = 0 when α₁₁ = 0 (no CSO clean-up) so C1 will be chosen; and
 (b) w₁ = w₃ = w₄ = w₅ = 0, and w₂ = 1 when α₁₁ = 1 so B2+FP3 will be chosen.
- ▶ Using utility function $U_2 = \sum_{j=1}^{5} w_j C_j \sum_{k=1}^{N_j} \alpha_{jk} B_{jk}$, the optimisation depends on B_{jk} and the weight/cost combinations $\alpha_{jk} B_{jk}$ (i.e. value judgements over 50yrs).
- ▶ What values should be assigned? How do we optimise U₂?
- Example: take $q_{1CSO} = 400k$, $q_{1k} = 50k$ (i.e. 1k/yr each) for i = 2, ..., 5 and $\alpha_{1k} = 1$ then **C1** wins.

Moreover, all these values will have uncertainties?

Bokhove, Leeds Institute for Fluid Dynamics, UK

Conclusion: utility functions High Beck

The emerging new insight using the straightforward utility function U_2 is as follows:

- The difference in costs between C1 (canal as flood storage with CSO-beck separation) and B2+FP3 (up- and downstream bunds and storage) is D =£135k.
- When we by choice are willing to assign the threshold value D =£135k to those combined C1 benefits (i.e. extra storage to deal with climate change effects, anti-drought measure, ecological effects and cleaner beck) over 50 years (i.e. £2.7k annually), then the two options have equal costs or value.
- ▶ When we by choice are willing to assign more than *D* =£135*k* to those combined benefits over 50 years, then option **C1** is best.
- That is just over £2.5k annually, which translation to annual costs makes the choice comprehensible (and pallatable).
- Alternatively, find (more than) $\pounds 135k$ of savings in the new flood-mitigation plans for the main river without sacrificing protection (possible).

▲□▶▲圖▶▲≣▶▲≣▶ ≣ のQ@

Bokhove, Leeds Institute for Fluid Dynamics, UK

Discussion

- Monster assimilation and adaptation are required to create decision problems that are sufficiently simple and well-structured.
- The High Beck case study exemplifies such adaptation through the square-lake cost-effectiveness analysis.
- However, acquisition of a minimal, apt amount of probabilities and costs and definition of comprehensible utility functions remains a open quest.
- Ultimately, simplicity and a good structure need to be maintained to allow comprehension by the decision makers beyond taking (engineering) advice based on faith/procedures as may often be the case in an approved process.
- Utility function U₂ yields valuable new insights ...



Bokhove, Leeds Institute for Fluid Dynamics, UK

Thank you!

PhD positions, one cohort starting each year for the next five years:

- Leeds' EPSRC Centre for Doctoral Training (CDT) in Future Fluid Dynamics offers a four-year integrated MSc with PhD programme.
- Please inquire; see https://fluid-dynamics.leeds.ac.uk/

▲□▶ ▲□▶ ▲目▶ ▲目▶ 三目 - のへで

Bokhove, Leeds Institute for Fluid Dynamics, UK